

**UNDER 10,001 GVW CHASSIS / HIGHROOF APPLICATION GUIDELINE (LONGBEDS)**

FORD TRUCKS WITH 8' BEDS				
MODEL	TYPE (4X2, 4X4, or Both)	CAB TYPE	GAS / DIESEL	MAX HEIGHT HIGHROOF
Ford F-250	Both	Regular Cab	Both	37" Highroof
Ford F-250	Both	Super Cab	Both	57" Highroof
Ford F-250	4X2	Crew Cab	Both	57" Highroof
Ford F-250	4X4	Crew Cab	Both	37" Highroof
Ford F-350	Both	Regular Cab	Both	37" Highroof
Ford F-350	Both	Super Cab	Both	57" Highroof
Ford F-350	4X2	Crew Cab	Both	57" Highroof
Ford F-350	4X4	Crew Cab	Both	37" Highroof

GM TRUCKS WITH 8' BEDS				
MODEL	TYPE (4X2, 4X4, or Both)	CAB TYPE	GAS / DIESEL	MAX HEIGHT HIGHROOF
GM 2500 C/K25903	Both *	Regular Cab *	Both *	46" Highroof
GM 2500 C/K25953	Both	Extended Cab	Gas	46" Highroof
GM 2500 C/K25953	Both	Extended Cab	Diesel	NONE
GM 2500 C/K25943	Both	Crew Cab	Gas	46" Highroof
GM 2500 C/K25943	Both	Crew Cab	Diesel	NONE
GM 3500 <10,001 GVW	Both	ALL	Both	NONE

\*Note: (\*) = C25903 that is (4X2) with (6.0L Vortec V-\*) and Exactly 10,000 GVW, Highroof "NOT PERMITTED!..."

RAM TRUCKS WITH 8' BEDS				
MODEL	TYPE (4X2, 4X4, or Both)	CAB TYPE	GAS / DIESEL	MAX HEIGHT HIGHROOF
RAM 2500	Both	Regular Cab	Both	60" Highroof
RAM 2500	Both	Crew Cab	5.7L Gas	60" Highroof
RAM 2500	4X2	Crew Cab	6.4L Gas	60" Highroof
RAM 2500	4X4	Crew Cab	6.4L Gas	53" Highroof
RAM 2500	Both	Crew Cab	6.7L Diesel	NONE

•Each manufacturer now uses the following to judge what is allowed and what is not:

- Center of Gravity
- Frontal Area
- Maximum Unloaded Vehicle Weight

•When calling with application questions, please have: Cab Type, Drive (4X2 or 4X4), GVWR, and Engine RPO available.

•Note: GM Shortbeds (42"CA / CST82 Bodies) will have to be handled Case-By-Case.

•Note: Please note that Trucks OVER 10,001 GVWR are currently NOT affected.

•Note: The above Chassis / Highroof Guideline ONLY applies to Under 10,001 GVW Chassis application (Longbed Trucks)...

•Note: Highroof Heights shown are maximum allowable...

•Note: Standard Highroof Heights are: 53", 60", and 74"...

•Note: Any other Highroof Heights are custom and would require Engineering (#SPL)...

•Contact your Inside Sales Representative for pricing on your Custom Height Highroof...

•Note: Floor to top of compartment on a Challenger ST II (Standard Height) is 25.5", so a 37" Highroof adds 11.5"...

•Note: On SRW trucks (Over 10,001 GVW), do NOT exceed 60" Highroof Height without consulting Inside Sales / Engineering...