

HD²

SNOWPLOW



THE BEST-SELLING FISHER® PLOW JUST GOT EVEN BETTER

Take everything you love about the FISHER HD Series snowplow, give it **two extra steel reinforcement ribs**, a **standard steel cutting edge** and a **full line of available accessories**, and you have the all-new HD2™ straight blade snowplow. The ultra-rugged HD2 plow features a high-strength powder coated steel moldboard with 10 vertical ribs for exceptional structural reinforcement and torsional strength. Available in 7' 6", 8', 8' 6" and 9' widths, there is an HD2 snowplow right for your vehicle.

The HD2 snowplow is the new standard in straight blade snow removal.

The Legacy Rolls On





BUILT FOR SERIOUS SNOW REMOVAL



HIGH-STRENGTH STEEL MOLDBOARD

The HD2™ plow is built of high-strength steel with STORM GUARD™ baked-on powder coat finish to help protect against wear and rust, keeping your blade looking newer, longer.

TRIP-EDGE PROTECTION

Fisher Engineering's industry-leading trip-edge design helps protect you and your equipment when encountering hidden obstacles. Since only the bottom edge trips, the blade stays upright and plowed snow remains in front of the blade, so there's less cleanup.

SKID-STEER MOUNTING PLATE



The HD2 plow is also available for skid-steers with a universal skid-steer mounting plate for fast and easy hook-up.

STANDARD CUTTING EDGE



Each FISHER® HD2 snowplow comes standard with a 1/2" steel cutting edge* made of high-carbon steel to provide extended cutting edge life.

*7' 6" HD2 model comes standard with a 3/8" steel cutting edge

FULL LINE OF ACCESSORIES

Trip-Edge Blade Wings | Back Drag Edge | Rubber Deflector | Steel Deflector | Steel SnoFoil® Deflector
Heavy-Duty Lift Ram | Curb Guards | Wear Shoes | 36" Commercial Blade Guides | Rubber Cutting Edge
Poly Cutting Edge | 5/8" Steel Cutting Edge | Carbide Cutting Edge

SPECIFICATIONS

Blade Width	Blade Height	Blade Gauge	Trip Springs	Ribs	Lift Cylinder	Angling Rams	Plowing Width (Full Angle)	Approximate Weight**	Cutting Edge	Wear Shoes
7' 6" (2.29 m)	29" (73.66 cm)	12 (2.66 mm)	3	10	1½" x 10" (3.81 cm x 25.40 cm)	1½" x 12" (3.81 cm x 30.48 cm)	6' 9" (2.05 m)	684 lb (310 kg)	3/8" x 6" steel (0.95 cm x 15.24 cm)	Optional
8' (2.44 m)	29" (73.66 cm)	12 (2.66 mm)	4	10	1½" x 10" (3.81 cm x 25.40 cm)	1½" x 12" (3.81 cm x 30.48 cm)	7' 2" (2.19 m)	734 lb (332 kg)	1/2" x 6" steel (1.27 cm x 15.24 cm)	Optional
8' 6" (2.59 m)	29" (73.66 cm)	12 (2.66 mm)	4	10	1½" x 10" (3.81 cm x 25.40 cm)	1½" x 12" (3.81 cm x 30.48 cm)	7' 7" (2.32 m)	750 lb (340 kg)	1/2" x 6" steel (1.27 cm x 15.24 cm)	Optional
9' (2.74 m)	29" (73.66 cm)	12 (2.66 mm)	4	10	1½" x 10" (3.81 cm x 25.40 cm)	1½" x 12" (3.81 cm x 30.48 cm)	8' 1" (2.46 m)	770 lb (349 kg)	1/2" x 6" steel (1.27 cm x 15.24 cm)	Optional

**Plus Vehicle Mount — Average 60 lb



Fisher Engineering | 50 Gordon Drive | Rockland, Maine 04841

fisherplows.com |



Fisher Engineering reserves the right under its product improvement policy to change construction or design details and furnish equipment when so altered without reference to illustrations or specifications used. Fisher Engineering or the vehicle manufacturer may require or recommend optional equipment for snow removal. Do not exceed vehicle ratings with a snowplow. This product is manufactured under the following US patents: 6,253,470; 6,944,978; 7,400,058; 7,430,821; 7,681,334; 7,737,576; 7,797,859; CAN patent 2,356,036. Fisher Engineering offers a limited warranty on all snowplows and accessories. See separately printed page for this important information. The following are registered (®) or unregistered (™) trademarks of Douglas Dynamics, LLC: FISHER®, HD2™, SnoFoil®, STORM GUARD™.