

THE RIGHT CHASSIS THE CORRECT SPECIFICATIONS FOR YOUR APPLICATION

TECHNICAL SPECIFICATIONS HAD - HAS SERIES

HOIST MODEL	CAPACITY	CONTAINER LENGTH	JIB HEIGHT	DUMP ANGLE
HAS 100 S	10,000 lbs.	10' - 12'	36 - 1/4"	50° - 38°
HAS 100 L	10,000 lbs.	11' - 13'	36 - 1/4"	52° - 46°
HAS 100 S SD	10,000 lbs.	10' - 12'	36 - 1/4"	50° - 38°
HAS 100 L SD	10,000 lbs.	11' - 13'	36 - 1/4"	52° - 46°
HAS 150	15,000 lbs.	12' - 14'	36 - 1/4"	52° - 43°
HAS 200 SS	20,000 lbs.	10' - 14'	36 - 1/4"	54° - 43°
HAS 200 S	20,000 lbs.	10' - 14'	54"	54° - 43°
HAS 200 M	20,000 lbs.	12' - 15'	54"	50° - 42°
HAS 200 L	20,000 lbs.	12' - 16'	54"	50° - 42°
HAD 130 S	13,000 lbs.	8' - 12'	36 - 1/4"	58°
HAD 130 L	13,000 lbs.	9' - 13'	36 - 1/4"	54°
HAD 185	18,500 lbs.	10' - 14'	36 - 1/4", 54"	58°
HAD 200 M	20,000 lbs.	10' - 14'	54"	58°
HAD 200 L	20,000 lbs.	12' - 16'	54"	56°
HAD 250 S	25,000 lbs.	12' - 16'	54"	56°
HAD 250 M	25,000 lbs.	14' - 18'	54"	49°
HAD 300 S	30,000 lbs.	12' - 16'	61 - 3/4"	56°
HAD 300 M	30,000 lbs.	14' - 18'	61 - 3/4"	49°

TECHNICAL SPECIFICATIONS TRUCK

HOIST MODEL	MIN. CA/CT	PLATFORM LENGTH	MIN. GVWR	MIN.F/R SUSP.	MIN. RBM
HAS 100 S	84" - 96"	126"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAS 100 L	96" - 108"	144"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAS 100 S SD	84" aft tank	132"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAS 100 L SD	108" aft tank	156"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAS 150	108" - 120"	156"	19,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAS 200 SS	108" - 120"	156"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAS 200 S	120"	155"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAS 200 M	120" - 130"	178"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAS 200 L	130" - 140"	182"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAD 130 S	84" - 96"	130"	19,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAD 130 L	108" - 120"	140"	19,500 lbs.	6K / 13.5K	500,000 in.lbs.
HAD 185	120" - 130"	158"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAD 200 M	120" - 130"	158"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAD 200 L	130" - 140"	180"	26,000 lbs.	8K / 18K	900,000 in.lbs.
HAD 250 S	CA = 138" - 140" / CT = N/A	183"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
HAD 250 M	CA = 168" - 170" / CT = N/A	203"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
HAD 300 S	CA = N/A / CT 126" - 132"	183"	52,000 lbs.	12K / 40K	1,000,000 in.lbs.
HAD 300 M	CA = N/A / CT 148" - 154"	203"	52,000 lbs.	12K / 40K	1,000,000 in.lbs.

TECHNICAL SPECIFICATIONS T-SERIES

HOIST MODEL	CAPACITY	CONTAINER LENGTH	JIB HEIGHT	DUMP ANGLE
CiTy	6,600 lbs.	9' - 11'	36 - 1/4"	50°
T 12 S	12,000 lbs.	10' - 12'	36 - 1/4"	52°
T 12 L	12,000 lbs.	12' - 14'	36 - 1/4"	48°
T 16 S	16,000 lbs.	11' - 14'	36 - 1/4"	52°
T 16 M	16,000 lbs.	12' - 16'	36 - 1/4"	49°
T 20 S	20,000 lbs.	11' - 14'	54"	52°
T 20 M	20,000 lbs.	12' - 16'	54"	49°
T 24 S	24,000 lbs.	11' - 14'	54"	50°
T 24 M	24,000 lbs.	12' - 16'	54"	50°
T 24 MT	24,000 lbs.	12' - 16'	36" & 54"	50°
T 24 L	24,000 lbs.	14' - 18'	54"	50°
T 30 S	30,000 lbs.	12' - 15'	54" / 61 - 3/4"	50°
T 30 L	30,000 lbs.	15' - 20'	54" / 61 - 3/4"	47°
T 40 S	40,000 lbs.	14' - 18'	54" / 61 - 3/4"	50°
T 40 L	40,000 lbs.	16' - 22'	54" / 61 - 3/4"	48°
T 50	50,000 lbs.	16' - 22'	54" / 61 - 3/4"	48°
T 60	60,000 lbs.	16' - 22'	54" / 61 - 3/4"	50°
G 68	68,000 lbs.	18' - 23'	61 - 3/4"	47°

TECHNICAL SPECIFICATIONS TRUCK

HOIST MODEL	MIN. CA/CT	PLATFORM LENGTH	MIN. GVWR	MIN.F/R SUSP.	MIN. RBM
CiTy	84"	115"	14,000 lbs.	5K / 9K	500,000 in.lbs.
T 12 S	84"	134"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
T 12 L	96" - 108"	153"	17,500 lbs.	6K / 13.5K	500,000 in.lbs.
T 16 S	108" - 120"	156"	22,000 lbs.	7K / 17K	750,000 in.lbs.
T 16 M	130" - 140"	187"	22,000 lbs.	7K / 17K	750,000 in.lbs.
T 20 S	108" - 120"	156"	26,000 lbs.	8K / 18K	750,000 in.lbs.
T 20 M	130" - 140"	187"	26,000 lbs.	8K / 18K	750,000 in.lbs.
T 24 S	110" - 120"	169"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
T 24 M	130" - 140"	181"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
T 24 MT	130" - 140"	181"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
T 24 L	150" - 160"	205"	33,000 lbs.	12K / 21K	1,000,000 in.lbs.
T 30 S	120" - 130"	173"	50,000 lbs.	12K / 38K	1,500,000 in.lbs.
T 30 L	150" - 160"	230"	50,000 lbs.	12K / 38K	1,500,000 in.lbs.
T 40 S	135" - 145"	212"	54,000 lbs.	14K / 40K	2,000,000 in.lbs.
T 40 L	180" - 190"	253"	54,000 lbs.	14K / 40K	2,000,000 in.lbs.
T 50	185" - 195"	253"	64,000 lbs.	18K / 46K	2,750,000 in.lbs.
T 60	185" - 195"	254"	64,000 lbs.	18K / 46K	2,750,000 in.lbs.
G 68	195" - 205"	254"	66,000 lbs.	20K / 46K	3,000,000 in.lbs.