



# Specifications

#### STANDARD CONSTRUCTION

•	Bulkhead	(non-ribbed	)14	ga. g	alvannea	l stee
	A		4.0			

- Compartment Bottoms.......16 ga. galvanneal steel
   Compartment Tops
   14 ga. galvanneal steel (one-
- Compartment Tops ......14 ga. galvanneal steel (one-piece integral with loadspace centers)
- Crossmember-front......7 ga. hot-rolled formed channels
- Crossmember-intermediate .12 ga. galvanneal steel
- Crossmember-rear.....7 ga hot-rolled formed channels
- Doors ......20 ga. galvanneal steel double panel
- End panels-front ......14 ga. galvanneal steel
- End panels-rear ......14 ga. galvanneal steel
- Fender panels......16 ga. galvanneal steel
- Floor......12 ga. embossed galvanneal treadplate
- Intermediate panels ......16 ga. galvanneal steel
- Loadspace inside centers .... 14 ga. galvanneal steel (one-piece integral with compartment tops)
- Longitudinals......10 ga. galvanneal formed
- Shelving ......14 ga. high-spangle galvanized (250# static load capacity)
- A-40 galvanneal construction. Two-sided zinc coated galvanneal (.40 oz zinc coating per square foot of steel) provides maximum rust and corrosion resistance.
- Body sides are constructed using plated lock-bolt fasteners.
- Floor understructure rigidly welded for structural integrity and durability. Mounting points re-inforced w/U-channel gussets.

### STANDARD FEATURES / EQUIPMENT

- Construction Lock-bolt to provide unbeatable durability, eliminates rust-causing welding and grinding, and promotes
  corrosion-free, long-lasting product. Floor understructure rigidly welded for structural integrity and undercoated for
  superior rust protection.
- Compartment Tops Smooth seamless surface to enhance appearance.
- **Cutouts** Openings in intermediate panels between horizontal and adjacent vertical compartments provides extended storage between compartments.
- Door Hinges Concealed, bolt-on style provides increased security and clean appearance
- Door Latches Bolt-on rotary style with stainless steel paddle handles and stainless steel pans.
- Lock Cylinders are keyed alike with double-bitted keys and are power door lock ready for easy after-market installation.
- Door Striker Adjustable, bolt-on.
- Vertical Doors Spring-loaded door holders to hold doors in the fully open position and assist in closing.
- Horizontal Doors Use vinyl coated aircraft quality cables for support in open position.
- Automotive Style Door Seal STAHL-engineered clip-on to allow easy removal for painting, replacement and quicker installation. Door seals against a flat surface for extra protection against water leakage.
- Drip Rail Concealed to provide extra protection against water leakage.
- Fender Panels Bolt-on die-stamped with radius wheel opening.
- Tailgate Two point slam-locking featuring anti-rack/rattle hardware.
- Shelving Bolt-in material trays with dividers.
- **Powder Coat Finish** Body exterior, compartment interiors, and cargo area surfaces are finished in a durable, corrosion resistant white powder coat.
- Undercoating On bottom of floor and wheelwells.
- **STAHL**'s 5-year limited warranty.

Continues on reverse side...



Shown with optional recessed lighted bumper

## STANDARD SHELVING PACKAGE

COMPARTMENT	BODY LENGTH	COMPT. WIDTH	CURBSIDE COMPARTMENTATION	STREETSIDE COMPARTMENTATION
Front vertical	98" 110" 134"	29.81" 33.44" 33.44"	(2) adjustable trays with dividers	(2) adjustable trays with dividers
Second vertical	134"	24.00"	(2) adjustable trays with dividers	(2) adjustable trays with dividers
Horizontal	ALL	47.19"	(1) adjustable tray with dividers	Open
Rear vertical	98" 110" 134"	21.00" 29.81" 29.81"	(1) adjustable tray with dividers	(1) adjustable tray with dividers

### **DIMENSIONAL SPECIFICATIONS**

DESCRIPTION	98VVS	98VVSLT	98VVD	110VVS	110VVD	110VVD	134VVD	134VVD
Overall Body Length	98"	98"	98"	110"	110"	110"	134"	134"
Loadspace Floor Width	48.50"	48.50"	52.50"	48.50"	48.50"	52.50"	48.50"	52.50"
Overall Body Width	79.98"	79.98"	96.00"	79.98"	92.00"	96.00"	92.00"	96.00"
Cab-to-axle	56.00"	56.00"	56.00"	60.00"	60.00"	60.00"	84.00"	84.00"
Front Vertical Width	29.81"	29.81"	29.81"	33.44"	33.44"	33.44"	33.44"	33.44"
Clear door opening	25.31"	25.31"	25.31"	28.94"	28.94"	28.94"	28.94"	28.94"
Second Vertical Width	n/a	n/a	n/a	n/a	n/a	n/a	24.00"	24.00"
Clear door opening	n/a	n/a	n/a	n/a	n/a	n/a	19.69"	19.69"
Horizontal Width	47.19"							
Clear door opening	45.31"							
Rear Vertical Width	21.00"	21.00"	21.00"	29.81"	29.81"	29.81"	29.81"	29.81"
Clear door opening	16.75"	16.75"	16.75"	25.56"	25.56"	25.56"	25.56"	25.56"
Vertical Compartment Height	39.50"	36.00"	39.50"					
Clear door opening	36.37"	31.13" *	36.37"					
Horizontal Compartment Height	18.07"	11.19" *	18.07"	18.07"	18.07"	18.07"	18.07"	18.07"
Clear door opening	14.94"	9.69" *	14.94"	14.94"	14.94"	14.94"	14.94"	14.94"
Side Compartment Depth (useable – above offset)	13.63"	13.63"	19.63"	13.63"	19.63"	19.63"	19.63"	19.63"
Floor-to-Compartment Top Height	25.50"	22.00"	25.50"	25.50"	25.50"	25.50"	25.50"	25.50"
Tailgate Height Above Floor	9.10"							
Tailgate Height Overall	11.22"							

<sup>\*</sup> Note: Top Pak clear door openings are from the bottom of the Top Pak pan.

### **OPTIONAL EQUIPMENT**

- Back Up Alarms
- Bar Lock Master Locking System
- Bumpers
- Crane Reinforcement (2,000-4,000#)
- Dome Lights
- Drawers
- Folding Steps & Grab Handles
- Fuel Fill (Alum.)
- Primer Paint

- High Roof
- Hitches
- Hooks
- Ladder Rack
- Light Kit LED
- Louvers
- Low Sliding Roof
- Off-Road Mounting Kit
- Shelves

- Paint and Installation
- Pipe Carrier
- Power Door Locks
- Tank Compartment
- Tie-Down Ring
- Tire Carrier
- Top Pak (add-on)
- Trays
- Treadbrite Overlay

Due to constant product evaluations and improvements, specifications are subject to change without notice.

