



SERIES IV PICKUP SPREADERS

The First And The Finest In Electric Spreaders Since 1986



Ready To Spread

**Flip-Up Chute Standard On
All Series IV Spreaders**

**No Mechanical Shaft Disconnect-
(Spinner Motor Swings With Chute)**



Chute In "Up Position"

All Stainless Steel Construction

The Smith Flip-Up Chute Makes it Easy To:

Tow A Trailer Without the Need of Removing The Spreader

Offload Unused Material

Store Spreader level And Safe When Not In Use

Series IV Spreader Standard Features

- **Stainless Steel Construction**

HOPPER, FRAME AND ALL STRUCTURAL COMPONENTS ARE CONSTRUCTED OF STAINLESS STEEL.

- **Pintle Chain Conveyor**

STEEL RIVETED PINTLE CHAIN WITH 3/16" x 1" CROSS BARS FOR CONSISTANT MATERIAL DELIVERY;
E-COATED FOR EXTENDED CHAIN LIFE.

- **Conveyor Drive System**

DUAL ELECTRIC: HIGH EFFIENENCY GEARBOX FOR MAXIMUM TORQUE, BUT REQUIRES LITTLE AMPERAGE.

DUAL HYDRAULIC: A WORN GEAR SPEED REDUCER IS USED FOR SMOOTH AND CONSISTANT OPERATION.

- **Inverted "V":** INCLUDED AS STANDARD EQUIPMENT.

- **Hot Dipped Galvinized Top Screen:** INCLUDED AS STANDARD EQUIPMENT

* **Optional Top Extention Kit and 24 Extended Flip Chute Shown**



OPTIONS

- * 24" EXTENDED CHUTE FOR DUMP BODY APPLICATIONS
- * 12" TOP EXTENSION FOR ADDED CAPACITY
- * FRONT AND REAR SPILL SHIELDS
- * SINGLE AND DUAL SPEED CONTROLS

GENERAL SPECIFICATIONS

Model	Hopper Capacity	Hopper Length	Hopper Height	Empty Weight
175	1 3/4 Yard	96"	33"	650 Lbs
300	3 Yard	96"	45"	750 Lbs

Distributed By:

**Distributed
by:**

CLIFFSIDE BODY CORPORATION

P.O. Box 206
130 Broad Avenue
FAIRVIEW, NEW JERSEY 07022
(201) 945-3970

Manufactured By:
Smith Metal Works
Smithspreaders.com