

Year-Round Performance For Utility Vehicles.

Add a Meyer<sup>®</sup> Drive Pro<sup>™</sup> plow to your utility vehicle and you have the perfect solution for plowing sidewalks, long driveways or any area where a pick-up truck is too large. Our contractor-grade plow features Meyer's easy-to-use 2", Class 3 receiver mount and is available in three moldboard sizes (5', 6' and 6' 8") to suite your application. Available with full hydraulics or self-angling.



Meyer's EZ-Mount receiver hitch allows you to remove or mount the Drive Pro plow in seconds.



## **EZ-Mount® Receiver Hitch**

comes on/off the vehicle in seconds by removing one pin.









Step 1: Insert or remove the pin Step 2: Position the wheels

Step 3: Connect/disconnect power plug

Step 4: Roll the plow away

## **One-Button Control**

All Drive Pros come standard with an ergonomically-designed pistol grip controller that features intuitive buttons to easily control the functions of the plow.

## Available in two options:

 Full power-angling controller allows the plow to go up/down, left/right like a traditional plow.



Self-angling controller allows the blade to go up/down by pressing a button. Right/left movement is controlled by the weight distribution of the snow on the plow.









The optional Self-Angling System senses the weight of the snow and automatically angles to push snow off to the side. Or, if you prefer, you can lock the plow in the direction you want.

Meyer Utility Plow Specifications										
Model #	Blade Type	Moldboard Length	Moldboard Height	Moldboard Gauge	Vertical Ribs	Plow Trip Springs	Cutting Edge	Average Width at Full Angle	Angling Rams	Weight Complete
DP-5.0	Full-Trip	5'0"	22.5"	14 Steel	6 per wing	2 per wing	1/4" x 6"	54"	1 3/4" x 8"	277 lb.
DP-6.0	Full-Trip	6'0"	22.5"	14 Steel	6 per wing	2 per wing	1/4" x 6"	65"	1 3/4" x 8"	285 lb.
DP-6.8	Full-Trip	6'8"	22.5"	14 Steel	6 per wing	2 per wing	1/4" x 6"	72"	1 3/4" x 8"	301 lb.

Weyer Snow Plows are protected by one or more of the following patents: 8006413, D0507999 S, D05179635, 8453358, 8695238, 7,918.042 B2, CA 2,677,509 C, D0517963 S, EP 1,989,402 B1, ES 2,346,587, 6138388, 7,591,087 B2, 7,661,211 B2, 7,793,440 B1, 8739437, 8739306, CA 2,604,085C, 6354024, 6276075, 6,318,975 B1, 6564479, 6256909, 6594923, 6618964, 7114270, 7117617, 7290359, D399326 S, CA 2,300,012 C, CA 2,314,772 C, CA 2,331,653, CA 2,370,925 C, CA 2,455,637 C, CA 2,653,801 C, CA 2,654,856, EP 1,010,809, 7353628, 6153975, 6273729, CA 2,280,509 C, CA 2,285,045 C, CA 2,283,838 C, CA 2,288,243 C, 6256829, 6015219, 6005300, 6163985.



Meyer Products LLC reserves the right under its continuing product improvement program to change construction or design details and specifications without incurring any obligation