



MINI MAX



AUGER SPREADER



MINI MAX SPREADERS

FEATURES & SPECIFICATIONS

Designed for utility vehicles and light duty pickup trucks, with the fewest moving parts of any spreader on the market today. This translates to minimum maintenance.

The Mini-Max is a “Vee-Box” salt spreader utilizing an auger for material delivery and separate 12 Volt Direct Current motors to power the auger and spinner.

Spreader construction:

16 gauge stainless steel

Auger is a 4 inch continuous flights mounted on a HD pipe

Hopper:

52 degree sides for continuous material flow

Vertical ends

Overall length will be an additional 23 inches with the “flip up” discharge chute attached

The flip up chute allows for:

- Trailer towing
- Discharge of unused material in a pile
- Ground storage (no stands needed)
- More rear clearance in the up position while plowing

Hopper dimensions:

All Mini-Max spreader are 33 inches wide
Low height (19 in.) allows spreader to be used under most tonneau covers if desired.



MINI MAX HOPPER VOLUME

Model Name	Length	Top Extension
Mini-Max — ¼ Yard	36”	Not Available
Mini-Max — ½ Yard	60”	Mini-Max — 1 Yard
Mini-Max — ¾ Yard	96”	Mini-Max — 1 ½ Yard

Available options for all Mini-Max spreaders:

- Spinner speed controller allows narrow pattern spreading
- Dual speed controller allows independent adjustment of auger & spinner
- A combination stainless steel cover & top extension is available for covering the ½ & ¾ yard spreaders.
- If needed, the cover/extension will increase capacity on the 60 inch hopper to one yard. The 96 inch hopper will increase to a full 1 ½ yard capacity.

Manufactured by:
Smith Metal Works
Of Newark, Inc.
1000 East Union Str.
Newark, NY 14513
<http://www.smithspreaders.com>
Established 1947

Distributed by

**Distributed
by**

CLIFFSIDE BODY CORPORATION

P.O. Box 206
130 Broad Avenue
FAIRVIEW, NEW JERSEY 07022
(201) 945-3970