GT # SLIDE-AWAY GATE



3,300 lb., 4,400 lb., and 5,500 lb. Capacities

Designed to Simplify Installation and Maximize Trailer Efficiency.



- Can be mounted on trailers with either swing-type or roll up doors
- Does not add to trailer length, making it ideal for 53-foot trailer applications
- Mounts easily to most dry-freight and refrigerated trailers
- Requires no modification of trailer sills up to 21 1/4" deep, and no moving of OEM lights or door hardware
- Requires only 64 1/2" to 77 1/2" behind the rear axle for mounting
- Large, single-fold, level ride platform featuring a rugged steel main section and a lightweight aluminum folding section
- Stores completely underneath the trailer eliminating the potential for backing damage at loading docks
- It allows you to completely seal at cushioned docks
- Since it is shipped completely assembled and tested from the factory, installation is significantly simplified
- Bolt on design allows easy removal and/or transfer
- Powder coat finish on key liftgate comonents produces a high-quality finish that is exceptionally resistant to corrosion and abrasion



Stores Completely **Underneath Trailer**



Powers Out from **Under Trailer**



Manually Unfold **Aluminum Extension**



Liftgate Positioned for Cargo Loading



Large level ride platform makes it ideal for a wide variety of trailer distribution applications.

Stored completely underneath the trailer, the GT Slide-Away Gate does not add to trailer length and requires no modification of trailer sills. OEM lights or door hardware.



Mounting the GT requires only 64 1/2" behind the rear axle



GT & SLIDE-AWAY GATE



Stores completely underneath the trailer



Thermally protected power unit



Optional Two-Piece Retention Ramp in the "up" position

Waltco Sales T: 800.211.3074 F: 800.211.3075 Email: sales@waltco.com Web: www.waltco.com

SPECIFICATIONS Bed Ht: 45"-64"

Model	Capacity	Platform	Ramp
GT - 33	3,300 lbs.	70" x 80"	12" Folding
GT - 33	3,300 lbs.	80" x 80"	12" Folding
GT - 44	4,400 lbs.	70" x 80"	12" Folding
GT - 44	4,400 lbs.	80" x 80"	12" Folding
GT - 55	5,500 lbs.	70" x 80"	12" Folding
GT - 55	5,500 lbs.	80" x 80"	12" Folding

Typical Ground Clearance Dimensions:

48" bed height has 17 1/4" ground clearance' 55" bed height has 24 1/4" ground clearance

OTHER STANDARD FEATURES:

- Thermally protected power unit safeguards liftgate motor from damage due to heat build-
- Reduced Maintenance™ features including: self-lubricating, fiberglass-reinforced Teflon® bearings at key pivot points and closed-loop hydraulic system
- Factory-installed fully-sealed raise/lower, open/close switches
- Super Duty Motor for increased motor run time and less wear and tear in high cycle applications
- Weather protective enclosure to shield power unit and vital components from environmental damage
- Electrical Wiring meets or exceeds all TMC Recommended Practices, including 150-amp circuit breaker protection
- (2) 12-Volt Group 31 Batteries
- DOT Certified, depending on bed height and "A" dimension

OPTIONAL EQUIPMENT:

- Canadian Rear Impact Guard Configuation
- Two-Piece Retention Ramp
- Platform Lights
- Hand Held Remote
- Dual Pump, Power Down Option for reliable performance in cold weather
- Trail Charger Kit provides a fully regulated 14-volt, 20-amp charge rate to remote liftgate batteries
- Power Down
- Customized Options contact factory
- Galvanized Option

Waltco Lift Corp. Corporate Office United States United States 285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418

Waltco Lift Corp. 620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149

Waltco Lift Inc. Canada 265 Export Blvd. Mississauga, ON L5S 1Y4 P: 888.343.4550

