# RGL<sup>SS</sup> RAIL GATE HEAVY DUTY



2,000 lb. - 6,600 lb. Capacities



## Large, Level-Ride, Low-Profile Platforms

## **STANDARD RGL SERIES ADVANTAGES INCLUDE:**

- Power up / gravity down hydraulic system
- Platform opens and closes hydraulically with no cam mechanisms to wear or become misaligned
- Frame rail constructed of rugged 3/8" steel
- Rigid steel linkage on sides of 2-piece platform provides greater load stability
- External slide bearing simplifies maintenance and eliminates hard to access internal rollers
- Coated galvanized cable assemblies
- All wiring and connections meet or exceed all TMC recommended practices
- Weather-protective power unit enclosure
- Reduced Maintenance features including: self-lubricating, fiberglassreinforced bearings at key pivot points
- Charge line circuit protection
- 12" Fixed Ramp standard on most 2-piece platform models
- Super Duty Motor
- Powder coat finish on key liftgate components produces a high-quality finish that is exceptionally resistant to corrosion and abrasion
- Cycle counter for maintenance tracking and planning
- Dedicated ground simplifies installation resulting in quicker, easier installs

SLIMLINE LEVEL RIDE (Standard)



Platform remains level from vehicle bed to the ground.

Increase productivity with simplified handling of bulky, wheeled, and palletized loads.



RGL Series Gate in stowed position



# RGL<sup>#</sup> HEAVY DUTY **RAIL GATE SPECIFICATIONS:**

Aluminum Ramp Shown

#### Bed Ht: 36"-60" (for non-dock loading) Bed Ht: 46"-60" (for dock loading)

| Model    | Capacity   | Platform  | Ramp |
|----------|------------|-----------|------|
| RGL-30   | 3,000 lbs. | 36" x 90" | 6"   |
| RGL-30   | 3,000 lbs. | 42" x 90" | 6"   |
| RGL-30   | 3,000 lbs. | 48" x 90" | BE   |
| RGL-30   | 3,000 lbs. | 60" x 90" | 12"  |
| RGL-30   | 3,000 lbs. | 72" x 90" | 12"  |
| RGL-40   | 4,000 lbs. | 42" x 90" | 6"   |
| RGL-40   | 4,000 lbs. | 48" x 90" | BE   |
| RGL-40   | 4,000 lbs. | 60" x 90" | 12"  |
| RGL-40   | 4,000 lbs. | 72" x 90" | 12"  |
| * RGL-50 | 5,000 lbs. | 60" x 90" | 12"  |
| * RGL-50 | 5,000 lbs. | 72" x 90" | 12"  |
| * RGL-50 | 5,000 lbs. | 84" x 90" | BE   |
| *RGL-60  | 6,000 lbs. | 60" x 90" | 12"  |
| *RGL-60  | 6,000 lbs. | 72" x 90" | 12"  |
| *RGL-60  | 6,000 lbs. | 84" x 90" | BE   |

Note: • 42"-48" deep platforms require a minimum 52" bed height for dock loading

- BE refers to Butt End style ramp
- Requires Rail Extension Kit when mounted on bed heights above 53" (RGL 50's and 60's have a max bed level of 58")

### **OPTIONAL EQUIPMENT:**

- 102" Wide Vehicle Option (increases steel platform widths to 96")
- Foot-Activated Cart Stops (available only on models with 12" fixed ramps)
- 16" Aluminum Folding Ramp reduces ground-to-platform incline
- Auxiliary Pump & Motor Unit with Pendant Control: Industry's only backup power system complete with secondary control switches
- Bottom Stops allow operator to lower the folded platform into a pre-set dock loading position
- (\*) Rail Extension Kit required for RGL-50, RGL-60 on bed heights greater than 53"
- Auxiliary Battery Power Kits for either straight truck or trailer applications
- Customized Options contact factory

#### Waltco Lift Corp. Corporate Office United States United States 285 Northeast Ave. Tallmadge, OH 44278 P: 330.633.9191 F: 330.633.1418

# Waltco Lift Corp.

620 S Hambledon Ave. City of Industry, CA 91744 P: 626.964.0990 F: 626.964.0149

Waltco Lift Inc. Canada 265 Export Blvd. Mississauga, ON L5S 1Y4 P: 888.343.4550

