



SPECIFICATIONS

- Turn your 8' pickup box into a 6,000 lb. capacity dump truck.
- Completely hidden installation raises the box only ¼", retaining the original look of your pickup.
- Engineered exlusively for 1999 to 2014 Ford Super Duty F Series ensuring a professional installation and perfect fit.
- Other models available for Chevrolet and GMC.
- Easy bolt-on installation no welding of truck frame or pickup body.
- Integrated lifting plate, hinge assembly and body stiffener forms a rugged body understructure to rigidly support the pickup floor.
- Flatbed conversion kit available
- Bumper brackets maintain original bumper location and class 2 hitch capability.
- Electric/Hydraulic pump offers industrial strength performance in your choice of:
 - ES Single-acting (Gravity down)
 - ED Double-acting (Power down)
- The VP6F is not applicable for the 2017 Ford trucks.

In order to comply with the 2015 Ford Super Duty F-Series Incomplete Vehicle Manual FMVSS (Federal Motor Vehicle Safety Standard) 301 Fuel System Integrity, installation of the Venco VP hoist is prohibited on trucks with a GVWR of 10,000 lbs. or less, because the hoist requires modification to some or all of the following: fuel tank attachment hardware, fuel filler cap, pipe, hose, attachment hardware and/or trailer hitch receiver. For more details, please consult the Ford Super Duty F-Series Incomplete Vehicle Manual, March 2014, FC34-19A268-AB.



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.





SPECIFICATIONS

- Turn your 8' pickup box into a 6,000 lb. capacity dump truck.
- Completely hidden installation raises the box only ¼", retaining the original look of your pickup.
- Designed exclusively for the 1999 and 2000 Chevrolet Silverado and GMC Sierra ensuring easy installation and a perfect fit.
- Designed for the 2004/05 Diesel Only
- Easy bolt-on installation no welding.
- Integrated lifting plate, hinge assembly and body stiffener forms a rugged body understructure to rigidly support the pickup floor.
- Bumper relocation kit and body skirt allows 45° dump angle.
- Electric/Hydraulic pump offers industrial strength performance in your choice of:
 - ES Single-acting (Gravity down)
 - ED Double-acting (Power down)



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.





SPECIFICATIONS

- Complete custom engineering, ensuring proper installation and perfect fit
- Heavy duty 6,000 lb. capacity
- 45° dumping angle
- Integrated hinge and bumper brackets
- Greaseless composite bearings in the hinges
- Integrated lifting nest, hinge assembly and body stiffener forms rugged body understructure to rigidly support pickup floor
- Bumper relocation kit maintains original look of vehicle and Class II hitch rating
- In-cab electronic controls; handheld pendant controller comes standard
- Safety prop (standard)
- New design requires minimal welding, speeding installation by an hour or more
- 3 1/2" diameter cylinder, 12-7/8" stroke operating at 2800 PSI (Double acting option operates at 650 PSI down pressure)
- Factory assembled variable width mounting base adapts to original cross member
- One-piece unitized upper nest insures maximum support to pickup body
- Built-in tapered guides standard
- Heavy-duty 12 volt electric hydraulic single-acting and double-acting pumps



CAUTION: THE COMBINED WEIGHTS OF TRUCK, BODY, HOIST AND LOAD MUST NOT EXCEED THE GROSS VEHICLE WEIGHT RATING (GVWR) OF THE TRUCK.